

SE-1200 EXPRESS / SE-1200

ECG MONITORS

SE-1200 EXPRESS KEY FEATURES:

- Easy to use with 8" colour touch screen, integrated file manager, and full size keyboard
- Highly accurate, sensitive and clear waveform (Fast 24-bit A/D transfer technology)
- Advanced algorithms used for Interpretation and measurements (included)
- Open communication with data export in PDF, SCP and FDA-XML through LAN/WiFi connectivity
- Extensive memory storing up to 200 ECG
- Heart rate variability (HRV) analysis
- Simple file sharing – ECG can be copied to a memory stick in PDF format
- Advanced Algorithms used for Interpretation and measurements (included)

SE-1200 KEY FEATURES:

- Easy to use with 5.7" LCD, integrated file manager, and full size keyboard
- Highly accurate, sensitive and clear waveform (Fast 24-bit A/D transfer technology)
- Advanced algorithms used for Interpretation and measurements (included)
- LAN connection to interface with PC and Smart ECG Viewer (Data management software)
- Memory storing up to 100 ECG
- Advanced algorithms used for Interpretation and measurements (included)



SE-1200 Express

- **One touch operation**
- **Touch Screen**



EDAN SE-1200 EXPRESS

CAT. No.	DESCRIPTION
ED-SE-1200Express	SE-1200Express ECG Monitor

EDAN SE-1200

CAT. No.	DESCRIPTION
ED-SE-1200	SE-1200 ECG Monitor

TROLLEY OPTION MT 201

CAT. No.	DESCRIPTION
ED-03.28.111847	Rolling Stand MT-201
ED-02.04.111902	Cable Arm for MT-201

TECHNICAL SPECIFICATIONS

ECG MONITORS

SE-12 Express Twelve Channel ECG	
Acquisition Mode	Simultaneous 12 lead acquisition (10-24 seconds adjustable)
Recording Mode	Auto/Manual/Rhythm/R-R Analyse
Sensitivity	2.5, 5, 10, 20, 10/5, AGC (mm/mV)
Filter	EMG filter 25Hz/35Hz/45Hz/OFF, DFT filter 0.05/0.15/0.25/0.5/0.32/0.67Hz Lowpass filter 150Hz/100Hz/75Hz, AC filter 50Hz/60Hz
Rhythm Lead	Single lead or three leads selectable
Power Supply	AC: 100V-240V, 50/60Hz
Battery	Built in rechargeable Li-ion battery; voltage=14.8V, for about 400 copies ECG printing
Printer	Thermal printer - Z-fold or roll paper A4
Speed	5mm/s, 10mm/s, 12.5mm/s, 25mm/s, 50mm/s (± 3%)
Display	800 x 600 TFT colour LCD
External Input/Output	Input: > 100K Ω ; Sensitivity 10mm/V ± 5% Output: < 100 Ω ; Sensitivity 1V/mV ± 5%
Communication ports	Ethernet, RS232, USB (WIFI optional)
Safety Standards	IEC 60601-1: 1988+A1+A2, EN 60601-1:1990+A1+A2, IEC/EN60601-2: 2001+A1, IEC/EN60601-2-25, ANSI/AAMI EC-11
Certificate	Australia TGA: ARTG 178086 Class IIa
Dimension	420mm x 330mm x 120mm
Weight	Approximately 6.5kg (excluding recording paper and battery)

SE-1200 Twelve-Channel ECG & SE-1200 Express Twelve-Channel ECG	
Acquisition Mode	Simultaneous 12 lead acquisition (10-24 seconds adjustable)
A/D Converter	24 bits
Sensitivity	2.5, 5, 10, 20, 10/5, AGC (mm/mV)
Filter	EMG filter 25Hz/35Hz/45Hz/OFF DFT filter 0.05/0.15/0.25/0.5/0.32/0.67Hz Lowpass filter 150Hz/100Hz/75Hz filter 50Hz/60Hz
Recording Mode	Auto/Manual/Rhythm/R-R
Rhythm Lead	Single lead or three leads selectable
Power Supply	AC: 100V-240V, 50/60Hz
Battery	Built-in rechargeable Li-ion battery; (approx. printing 300 ECG)
Printer	Thermal printer - A4 roll paper and Z-fold
Speed	5mm/s, 6.25mm/s, 10mm/s, 12.5mm/s, 25mm/s, 50mm/s (± 3%)
Dimension	420mm x 330mm x 120mm WIFI Optional
Display	5.7" 320 x 240 dots monochrome LCD
Communication ports	Ethernet, RS232, USB
Safety Standards	IEC 60601-1: 1988+A1+A2, EN 60601-1:1990+A1+A2, IEC/EN60601-2: 2001+A1, IEC/EN60601-2-25, ANSI/AAMI EC-11 Australia TGA: ARTG 178086 Class IIa
Certificate	Australia TGA: ARTG 178086 Class IIa
Weight (after dimension)	Approximately 5kg